




This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0079	UPDATED TO NEW STANDARD, CH'D DIM WAS M30X1.5 IS M30X1.5-6H, CH'D DIM WAS M105 X 1.5 IS M105 X 1.5-6H, ADDED DIM 1.63, REMOVED DIM .313 & Ø 4.063, ADDED MIN RELIEF. CH'D MAT'L WAS 4140 IS 4140/4142 RC 28-34. ADDED FINISH & SPEC.	7/18/2016	DEW	SM



## SECTION A-A

NOTE:  
USED IN KIT RBEA62316



## RELEASE MECHANISM

DWG NO.

RBE1X53-174-739-1

RE<sup>2</sup>

MAT'L 4140/4142		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
HEAT RC 28-34		.000 ± .005 FRACTIONS ± 1/8	
TREAT		.00 ± .01 ANGLES ± 5°	
FINISH BLACK OXIDE		X ± .1 SURFACES = 125 ✓	
SPEC QMSI-6.2.2 REV D		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
DRAWN BY:	GILBERT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
CHECKED:	CLOUGH	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
OPPS APPR:	ANDERSON		
QA APPR:	LINDSAY	USED ON MODEL	
APPROVED:	MACKOVJAK	EC135	
SCALE	1:2	DATE	6/14/2012
		SHEET 1 OF 1	